

Special skirting tape for floor covering strips in DÖLLKEN skirting rails

# Contact 40

Securely bonding of floor covering strips in DÖLLKEN skirting rails

## Applications:

Special acrylic adhesive system for the quick and reliable installation of skirting strips for carpets and resilient floor coverings. Contact allows quick and clean working without solvents. For interior applications.

### ► Suitable carpet and floor covering strips in DÖLLKEN core skirting boards TS 60/TS 100:

- With fleece backing
- With synthetic double backing (SDR)
- With textile secondary backing (TR)
- With latex foam backing
- Needle punch
- Kugelgarn® and Kugelvlies®
- Woven textile floor coverings

Recommendation: use TS 100 Contact 85 to glue the specified carpet strips in DÖLLKEN carpet skirting.

### ► Suitable floor covering strips in DÖLLKEN core skirting strips C 60/D 60:

- PVC/CV
- PVC design covering
- Rubber
- Linoleum
- DÖLLKEN colour strips
- MEDES-Alu-Floor

Item	Tape width	Skirting height
Contact 40	40 mm	45 mm – 55 mm
Contact 55	55 mm	60 mm – 70 mm
Contact 70	70 mm	75 mm – 85 mm
Contact 85	85 mm	90 mm – 110 mm

Provides the highest possible level of emission safety and contributes towards creating a healthy room climate. Marked with the "Blue Angel" for low-emission floor covering adhesives and other installation materials according to RAL-UZ 113.



**ÖKOLINE**

for floor covering strips  
ON DÖLLKEN core skirting boards TS 60/C 60/D 60

**Ingredients:** Acrylic copolymers, wetting and defoaming agents, laid scrims, paper.

## Product benefits / Features:

- Does not become brittle, providing a strong & permanent bond
- For PVC and CV floor coverings, PVC luxury floor coverings, linoleum and colour strips in C 60/D 60
- For needle punch, SDR, TR and fleece backing, woven carpets in TS 60/TS 100
- DÖLLKEN-UZIN System Guarantee
- Solvent-free / complies with TRGS 610 (technical regulation for dangerous substances)
- "Blue Angel" as per RAL-UZ 113
- EMICODE EC 1 PLUS / very low-emission

## Technical specifications:


Packaging:	carton
Width of rolls:	40 mm / 55 mm / 70 mm / 85 mm
Length of rolls:	50 m
Shelf life:	min. 2 years
Colour:	transparent
Substrate temperature:	min. 15°C
Open time:	none
Working time:	none
Set to traffic:	immediately after bonding
Sealing / jointing seams:	immediately after bonding

## Notes for preparation:

- ▶ Substrate preparation: The substrate must be permanently dry, hard, load-bearing, flat, free from grease, dust and silicon, in accordance with the respective national standards (EN, DIN, VOB, OE, SIA).
- ▶ Wallpapers: must be firmly bonded.
- ▶ Bind dust with a solvent-free primer (e.g. UZIN PE 260).
- ▶ Ensure the floor covering and Contact 40 are free from contortions before installing. Allow the floor covering (and Contact 40) to acclimatise sufficiently according to the manufacturers recommendations.

## The following is needed:

- ▶ Contact 40, rubber mallet, carpet knife



## Application:

- ▶ Floor covering strips: Always cut the individual floor covering strips lengthways or walking direction.
- ▶ Outside corners: Notch elastic strips at the back (relief), warm them and bond without twisting.
- ▶ Pre-bend textile strips.
- ▶ Inside corners: Cut through strips and join with instant glue.
- ▶ Compositions:
  - Bond PVC/CV strips
  - Join rubber strips and colour strips with instant glue
  - Do not bond design covering strips

## Installation of TS 60/TS 100 and C 60/D 60



- ▶ TS 60/TS 100: Apply Contact to the backing of the carpet skirting
- ▶ C 60/D 60: Install Contact 40 by hand directly in the DÖLLKEN skirting board C 60/D 60
- ▶ Do not yet remove the protective paper



- ▶ Pull off the two protective papers continuously
- ▶ Install carpet skirting or floor covering strip into the DÖLLKEN core skirting board, without stressing or twisting



- ▶ Tap in everywhere using the rubber mallet  
→ doubles the adhesive strength

## Contact applicator:



## Important notes:

- ▶ **Not guaranteed:**
  - Wooden strips
  - Carpet skirting with PU backing
  - Dirt trap runners
  - PVC soft skirting boards

Store in a dry, cool area without exposure to direct sunlight.

## Protection of the workplace and the environment:

The product does not require any special labour protection measures. For reasons of working hygiene, we recommend avoiding eating, drinking and smoking during processing of this product. Store out of the reach of children.

For more information refer to [www.uzin.com](http://www.uzin.com) or contact +49 (0)731 4097-0

## Disposal:

Empty shells and the cardboard packaging can be recycled. Material remnants can be disposed of as household waste.

## Warranty:

**UZIN and Döllken guarantee all properties stated in the installation instructions for a period of 5 years.**

- Follow the generally acknowledged rules of the trade and of technology for the installation of floor covering of the respective applicable standards (EN, DIN, VOB, OE, SIA).

In all cases, some adhesion tests must be carried out on-site before carrying out the installation.

The warranty becomes void if:

- the product is exposed to unusual impact especially of chemical or mechanical nature.
- used or processed differently than stated in the installation instructions.
- Contact 40 may only be used as supplement on stairs.
- Moisture affects Contact 40.
- installation was performed below 15°C (on the wall).
- Contact 40 is used in areas with increased humidity or thermal exposures (e.g. conservatories).